

MX-EX

With ex-approved plastic-skid pallet

SCHÜTZ
INDUSTRIAL PACKAGING

The Future's Technology. Today.

www.schuetz.net

MATERIAL

Inner bottle

- Inner and intermediate layer: high-molecular, high-density polyethylene (HDPE)



- Antistatic / conductive outer layer

- Additional UV and light protection of the filling product (optional)

Optional

- EVOH permeation barrier



PALLET (4-way entry)



NEW! SCHÜTZ plastic pallets – now available for ex-zones!



- The IBC is earthed by metal contact plates in the outer runners
- Giving full ex-protection even when the IBCs are stacked
- Environmentally friendly through the use of high-quality recycle material from our reconditioning service
- Exceptionally stable and impact resistant
- Very good resistance to chemicals
- Hygienic and corrosion resistant
- Pallet has excellent liftability

Please do not hesitate to contact us regarding any technical concerns or questions.

CERTIFICATIONS

- UN 31HA1/Y (optional)
- Maximum density 1.6
- Tested for electrostatic safety
- Suitable for use in ex-zones 1 & 2



IIA

CAPACITY

- MX-EX antistatic / conductive 1000
- 1,000 litres (275 gal)

OUTLET VALVES

- Earthed screwable butterfly valve DN 50
- Earthed screwable butterfly valve DN 80

FILLING OPENING


- DN 150 with screw cap
- DN 225 with screw cap

DYNAMIC LOAD

Filled ECOBULK according to the specific weight of the filling goods

DIMENSIONS

- 1,200 x 1,000 x 1,160 (L x W x H)



WEIGHT

- MX-EX antistatic / conductive 1000
- 59 kg with plastic pallet

STATIC LOAD

- Max. 4-high

